

TYRES

Product group	Tyres
Item number	15735255
Valid tyre size	540 / 70 R 24
LI / SI / PR	168 A8 / 168 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522



Notes and features

- Agro-industrial / MPT tyres for telescopic handlers, wheel loaders and backhoe loaders.
- Radial carcass with reinforcing steel belt for high load capacity and protection against puncture damage.
- Aggressive tread lugs for traction under any working conditions.
- Special rubber compound for hard terrain.
- Deep tread depth for a long service life.

Technical Informations

Item number	15735255
EAN	8903094052264
Valid tyre size	540 / 70 R 24
LI / SI / PR	168 A8 / 168 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	137,58
Recommended rim size	DW16L
Permitted rim size	DW18L
Maximum air pressure [bar].	4,00
Section width (mm)	530
Outer diameter of tyre [mm].	1366
Stat. radius (SLR) [mm]	611
Rolling circumference [mm].	4133
Tread depth (mm)	42,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	50		4,00	
168 B	5600	40		4,00	