

TYRES

Product group	Tyres
Item number	15735265
Valid tyre size	365 / 80 R 20
LI / SI / PR	152 K
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Earthmax SR 33 is a radial MPT tyre
- The block pattern provides very good traction on soft, sandy or muddy ground
- The wide spaces between the tread pattern blocks enable very good self-cleaning
- The strong, all-steel casing ensures excellent cut resistance and a long service life

Technical Informations

Item number	15735265
EAN	8903094061907
Valid tyre size	365 / 80 R 20
Alternative size 1	14.5R20
LI / SI / PR	152 K
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	81,97
Recommended rim size	10.0
Maximum air pressure [bar].	6,20
Section width (mm)	360
Outer diameter of tyre [mm].	1096
Stat. radius (SLR) [mm]	496
Rolling circumference [mm].	3318
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 K	3550	110		6,20	