

TYRES

Product group	Tyres
Item number	15735270
Valid tyre size	16.00 R 20
LI / SI / PR	173 / 170 G
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33 Plus



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Earthmax SR 33 Plus is a radial MPT tyre
- The block pattern provides very good traction on soft, sandy or muddy ground
- The wide spaces between the tread pattern blocks enable very good self-cleaning
- The strong, all-steel casing ensures excellent cut resistance and a long service life

Technical Informations

Item number	15735270
EAN	8903094064038
Valid tyre size	16.00 R 20
LI / SI / PR	173 / 170 G
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33 Plus
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	131,02
Recommended rim size	11.25
Permitted rim size	10.00W, 10.00
Maximum air pressure [bar].	7,60
Section width (mm)	448
Outer diameter of tyre [mm].	1310
Stat. radius (SLR) [mm]	582
Rolling circumference [mm].	3974
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 G	6500	90		7,60	
170 G	6000	90		7,60	