

TYRES

Product group	Tyres
Item number	15735305
Valid tyre size	445 / 95 R 25
LI / SI / PR	174 F
TL/TT	TL
Brand	BKT
Tread pattern	Airomax AM 27



Notes and features

- Excellent traction on- and off- road
- The special rubber compound allows for ideal protection from cutting damage and it prevents the tyre from overheating during longer road journeys
- Most suitable for use with mobile cranes
- This tyre has an E4 certification in accordance with ECE approval R54 - pneumatic tyres for utility vehicles and trailers

Technical Informations

Item number	15735305
EAN	8903094039043
Valid tyre size	445 / 95 R 25
Alternative size 1	16.00R25
LI / SI / PR	174 F
TL/TT	TL
Brand	BKT
Tread pattern	Airomax AM 27
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	206,27
Recommended rim size	11.25/2.0
Permitted rim size	11.00/1.7CR, 11.00/1.7CRL, 11.00/1.7 (einteilig)
Maximum air pressure [bar].	9,00
Section width (mm)	440
Outer diameter of tyre [mm].	1490
Stat. radius (SLR) [mm]	695
Rolling circumference [mm].	4587
Tread depth (mm)	23,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
174 F	6700	80		9,00	