

## TYRES

Product group	Tyres
Item number	15735344
Valid tyre size	480 / 80 R 26
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

## Technical Informations

Item number	15735344
EAN	8903094055012
Valid tyre size	480 / 80 R 26
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	141,74
Recommended rim size	DW15L
Permitted rim size	DW16L
Maximum air pressure [bar].	3,20
Section width (mm)	479
Outer diameter of tyre [mm].	1428
Stat. radius (SLR) [mm]	642
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4259
Tread depth (mm)	36,5
Number of lugs	28x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		3,20	
160 B	4500	50		3,20	