

TYRES

Product group	Tyres	
Item number	15770066	
Valid tyre size	16 x 6 - 8 / 4.33 R	
Brand	BKT	
Tread pattern	Maglift	



Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance ratio.
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.



Technical Informations

Item number	15770066
EAN	8903094036950
Valid tyre size	16 x 6 - 8 / 4.33 R
Alternative size 1	150/75-8
Brand	BKT
Tread pattern	Maglift
Carcass properties	LIP,Solid Rubber
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	14,85
Recommended rim size	4.33R
Section width (mm)	139
Side panel width [mm]	139
Tread width (mm)	118
Overall width [mm].	139
Outer diameter of tyre [mm].	421
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	1495	25	Load wheel		
	1150	25	Steering wheel		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.