

## TYRES

|                 |                       |
|-----------------|-----------------------|
| Product group   | Tyres                 |
| Item number     | 15770118              |
| Valid tyre size | 23 x 10 - 12 / 8.00 G |
| Brand           | BKT                   |
| Tread pattern   | Maglift               |



## Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance ratio.
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.

## Technical Informations

|                              |                       |
|------------------------------|-----------------------|
| Item number                  | 15770118              |
| EAN                          | 8903094050017         |
| Valid tyre size              | 23 x 10 - 12 / 8.00 G |
| Alternative size 1           | 250/60-12             |
| Brand                        | BKT                   |
| Tread pattern                | Maglift               |
| Carcass properties           | STD,Solid Rubber      |
| Antistatic                   | Yes                   |
| Tyre colour                  | Black                 |
| ECE regulation number        | not necessary         |
| Nettogewicht [kg] (gültig)   | 47,72                 |
| Recommended rim size         | 8.00G                 |
| Section width (mm)           | 236                   |
| Side panel width [mm]        | 236                   |
| Tread width (mm)             | 210                   |
| Overall width [mm].          | 240                   |
| Outer diameter of tyre [mm]. | 584                   |
| Tread depth (mm)             | 23,0                  |
| E-Ready                      | No                    |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position  | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|----------------|--------------------------|--------------|
|       | 3770               | 25           | Load wheel     |                          |              |
|       | 2900               | 25           | Steering wheel |                          |              |