

TYRES

Product group	Tyres
Item number	15770144
Valid tyre size	27 x 10 - 12 / 8.00 G
Brand	BKT
Tread pattern	Maglift



Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance ratio.
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.



Technical Informations

Item number	15770144
EAN	8903094054770
Valid tyre size	27 x 10 - 12 / 8.00 G
Alternative size 1	250/75-12
Brand	BKT
Tread pattern	Maglift
Carcass properties	LIP,Non-Marking,Solid Rubber
Antistatic	No
Tyre colour	Grey
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	72,58
Recommended rim size	8.00
Section width (mm)	240
Side panel width [mm]	236
Tread width (mm)	210
Overall width [mm].	240
Outer diameter of tyre [mm].	677
Tread depth (mm)	24,0
E-Ready	No

Load capacity

ı	ndex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
		3900	25	Load wheel		
		3000	25	Steering wheel		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.