

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15770153 |
| Valid tyre size | 7.50 - 15 / 6.0 |
| Brand | BKT |
| Tread pattern | Maglift |



Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance ratio.
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.

Technical Informations

| | |
|------------------------------|------------------------------|
| Item number | 15770153 |
| EAN | 8903094054527 |
| Valid tyre size | 7.50 - 15 / 6.0 |
| Brand | BKT |
| Tread pattern | Maglift |
| Carcass properties | STD,Non-Marking,Solid Rubber |
| Antistatic | No |
| Tyre colour | Grey |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 67,12 |
| Recommended rim size | 6.0 |
| Section width (mm) | 193 |
| Side panel width [mm] | 193 |
| Tread width (mm) | 172 |
| Overall width [mm]. | 193 |
| Outer diameter of tyre [mm]. | 756 |
| Tread depth (mm) | 26,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|----------------|--------------------------|--------------|
| | 3900 | 25 | Load wheel | | |
| | 3000 | 25 | Steering wheel | | |