## Bohnenkamp Moving Professionals

**TYRES** 

| Product group   | Tyres           |
|-----------------|-----------------|
| Item number     | 15770157        |
| Valid tyre size | 7.50 - 15 / 6.0 |
| Brand           | ВКТ             |
| Tread pattern   | Maglift         |



## Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance ratio.
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

**Technical Informations** 

| Item number                  | 15770157         |
|------------------------------|------------------|
| EAN                          | 8903094044436    |
| Valid tyre size              | 7.50 - 15 / 6.0  |
| Brand                        | ВКТ              |
| Tread pattern                | Maglift          |
| Carcass properties           | STD,Solid Rubber |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| ECE regulation number        | not necessary    |
| Nettogewicht [kg] (gültig)   | 66,18            |
| Recommended rim size         | 6.0              |
| Section width (mm)           | 193              |
| Side panel width [mm]        | 193              |
| Tread width (mm)             | 172              |
| Overall width [mm].          | 193              |
| Outer diameter of tyre [mm]. | 756              |
| Tread depth (mm)             | 26,0             |
| E-Ready                      | No               |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position  | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|----------------|-----------------------------|--------------|
|       | 3900               | 25           | Load wheel     |                             |              |
|       | 3000               | 25           | Steering wheel |                             |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

20.09.2024