

TYRES

Product group	Tyres
Item number	15770161
Valid tyre size	8.15 - 15 / 7.0
Brand	BKT
Tread pattern	Maglift



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance ratio.
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.

Technical Informations

Item number	15770161
EAN	8903094036547
Valid tyre size	8.15 - 15 / 7.0
Alternative size 1	28x9-15
Brand	BKT
Tread pattern	Maglift
Carcass properties	STD,Solid Rubber
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	56,75
Recommended rim size	7.0
Section width (mm)	218
Side panel width [mm]	218
Tread width (mm)	192
Overall width [mm].	218
Outer diameter of tyre [mm].	691
Tread depth (mm)	24,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	3445	25	Load wheel		
	2650	25	Steering wheel		