

## TYRES

Product group	Tyres
Item number	15770200
Valid tyre size	28 x 12.5 - 15 / 9.75
Brand	BKT
Tread pattern	Maglift



## Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance ratio.
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.

## Technical Informations

Item number	15770200
EAN	8903094051359
Valid tyre size	28 x 12.5 - 15 / 9.75
Alternative size 1	355/45-15
Brand	BKT
Tread pattern	Maglift
Carcass properties	STD,Solid Rubber
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	76,86
Recommended rim size	9.75
Section width (mm)	295
Side panel width [mm]	295
Tread width (mm)	274
Overall width [mm].	296
Outer diameter of tyre [mm].	687
Stat. radius (SLR) [mm]	324
Rolling circumference [mm].	2090
Tread depth (mm)	26,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	5690	25	Load wheel		
	4375	25	Steering wheel		