

## **TYRES**

| Product group   | Tyres                  |
|-----------------|------------------------|
| Item number     | 15771055               |
| Valid tyre size | 5.00 - 8               |
| LI / SI / PR    | 10 PR                  |
| TL/TT           | тт                     |
| SET             | Tube + Flap            |
| Brand           | BKT                    |
| Tread pattern   | Power Trax HD Forklift |



## **Notes and features**

- The BKT Power Trax HD Forklift is a premium tyre, designed for forklifts in industrial applications.
- Its deep tread pattern, extra thick sidewalls and tough casing protect the tyre from cuts, tears and punctures.
- The tyre is characterised by outstanding durability and is especially suitable for rough and hard concrete surfaces.
- The specially designed rim guard ensures protection against damage in the rim flange area.



## **Technical Informations**

| Item number                  | 15771055               |
|------------------------------|------------------------|
| EAN                          | 8903094007790          |
| Valid tyre size              | 5.00 - 8               |
| Alternative size 1           | 5.70-8                 |
| LI / SI / PR                 | 10 PR                  |
| TL/TT                        | тт                     |
| SET                          | Tube + Flap            |
| Ventilposition               | lateral                |
| Brand                        | BKT                    |
| Tread pattern                | Power Trax HD Forklift |
| Antistatic                   | No                     |
| Tyre colour                  | Black                  |
| ECE regulation number        | not necessary          |
| Nettogewicht [kg] (gültig)   | 8,19                   |
| Recommended rim size         | 3.00D                  |
| Permitted rim size           | 3.251                  |
| Maximum air pressure [bar].  | 10,00                  |
| Section width (mm)           | 145                    |
| Outer diameter of tyre [mm]. | 480                    |
| Tread depth (mm)             | 13,5                   |
| E-Ready                      | No                     |

## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position  | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|----------------|-----------------------------|--------------|
|       | 1415               | 25           | Load wheel     | 10,00                       |              |
|       | 1090               | 25           | Steering wheel | 10,00                       |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.