

TYRES

Product group	Tyres
Item number	15771070
Valid tyre size	6.00 - 9
LI / SI / PR	114 A8, 10 PR
TL/TT	тт
SET	Tube + Flap
Brand	BKT
Tread pattern	PL 801



Notes and features

- The BKT PL 801 was developed for forklifts, but is equally suitable for hay tedders and hay harvesting equipment.
- The tyre is characterised by its excellent stability.
- Its rubber compound offers very good resistance to punctures and cuts, ensuring a long service life.



Technical Informations

Item number	15771070
EAN	8903094007127
Valid tyre size	6.00 - 9
Alternative size 1	6.90-9
LI / SI / PR	114 A8, 10 PR
TL/TT	тт
SET	Tube + Flap
Valve designation	JS 2
Ventilposition	lateral
Brand	BKT
Tread pattern	PL 801
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	10,34
Recommended rim size	4.00E
Maximum air pressure [bar].	8,50
Section width (mm)	157
Outer diameter of tyre [mm].	543
Tread depth (mm)	14,0
E-Ready	No



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
114 A8	1180	40	Steering wheel	8,50	
	1715	25	Load wheel	8,50	
	1320	25	Steering wheel	8,50	