

## **TYRES**

| Product group   | Tyres       |
|-----------------|-------------|
| Item number     | 15771085    |
| Valid tyre size | 21 x 8 - 9  |
| LI / SI / PR    | 16 PR       |
| TL/TT           | ТТ          |
| SET             | Tube + Flap |
| Brand           | ВКТ         |
| Tread pattern   | PL 801      |



## Notes and features

- The BKT PL 801 was developed for forklifts, but is equally suitable for hay tedders and hay harvesting equipment.
- The tyre is characterised by its excellent stability.
- Its rubber compound offers very good resistance to punctures and cuts, ensuring a long service life.



## **Technical Informations**

| Item number                  | 15771085      |
|------------------------------|---------------|
| EAN                          | 8903094027842 |
| Valid tyre size              | 21 x 8 - 9    |
| Alternative size 1           | 200/75-9      |
| LI / SI / PR                 | 16 PR         |
| TL/TT                        | ТТ            |
| SET                          | Tube + Flap   |
| Valve designation            | JS 2          |
| Ventilposition               | lateral       |
| Brand                        | BKT           |
| Tread pattern                | PL 801        |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | not necessary |
| Nettogewicht [kg] (gültig)   | 14,92         |
| Recommended rim size         | 6.00E         |
| Permitted rim size           | 7.00E         |
| Maximum air pressure [bar].  | 10,00         |
| Section width (mm)           | 200           |
| Outer diameter of tyre [mm]. | 535           |
| Tread depth (mm)             | 19,0          |
| E-Ready                      | No            |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position  | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|----------------|-----------------------------|--------------|
|       | 2755               | 25           | Load wheel     | 10,00                       |              |
|       | 2120               | 25           | Steering wheel | 10,00                       |              |