

TYRES

Product group	Tyres	
Item number	15771093	
Valid tyre size	6.50 - 10	
LI / SI / PR	10 PR	
TL/TT	тт	
SET	Tube + Flap	
Brand	BKT	
Tread pattern	Power Trax HD Forklift	





Notes and features

- The BKT Power Trax HD Forklift is a premium tyre, designed for forklifts in industrial applications.
- Its deep tread pattern, extra thick sidewalls and tough casing protect the tyre from cuts, tears and punctures.
- The tyre is characterised by outstanding durability and is especially suitable for rough and hard concrete surfaces.
- The specially designed rim guard ensures protection against damage in the rim flange area.



Technical Informations

Item number	15771093
EAN	8903094007813
Valid tyre size	6.50 - 10
LI / SI / PR	10 PR
TL/TT	ТТ
SET	Tube + Flap
Valve designation	JS 2
Ventilposition	lateral
Brand	ВКТ
Tread pattern	Power Trax HD Forklift
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	16,39
Recommended rim size	5.00F
Permitted rim size	5.50F
Maximum air pressure [bar].	7,75
Section width (mm)	193
Outer diameter of tyre [mm].	595
Stat. radius (SLR) [mm]	278
Rolling circumference [mm].	1774
Tread depth (mm)	17,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	1950	25	Load wheel	7,75	
	1500	25	Steering wheel	7,75	