

TYRES

Product group	Tyres	
Item number	15771096	
Valid tyre size	23 x 9 - 10	
LI / SI / PR	20 PR	
TL/TT	тт	
SET	Tube + Flap	
Brand	BKT	
Tread pattern	Power Trax HD Forklift	





Notes and features

- The BKT Power Trax HD Forklift is a premium tyre, designed for forklifts in industrial applications.
- Its deep tread pattern, extra thick sidewalls and tough casing protect the tyre from cuts, tears and punctures.
- The tyre is characterised by outstanding durability and is especially suitable for rough and hard concrete surfaces.
- The specially designed rim guard ensures protection against damage in the rim flange area.



Technical Informations

Item number	15771096
EAN	8903094007714
Valid tyre size	23 x 9 - 10
Alternative size 1	225/75-10
LI / SI / PR	20 PR
TL/TT	тт
SET	Tube + Flap
Valve designation	TR 177 A
Ventilposition	central
Brand	BKT
Tread pattern	Power Trax HD Forklift
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	23,88
Recommended rim size	6.50F
Maximum air pressure [bar].	10,00
Section width (mm)	235
Outer diameter of tyre [mm].	590
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	3445	25	Load wheel	10,00	
	2650	25	Steering wheel	10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.