

TYRES

Product group	Tyres
Item number	15771100
Valid tyre size	7.00 - 12
LI / SI / PR	130 A8, 14 PR
TL/TT	TT
SET	Tube + Flap
Brand	BKT
Tread pattern	PL 801



Notes and features

- The BKT PL 801 was developed for forklifts, but is equally suitable for hay tedders and hay harvesting equipment.
- Its rubber compound offers very good resistance to punctures and cuts, ensuring a long service life.
- The tyre is characterised by its excellent stability.

Technical Informations

Item number	15771100
EAN	8903094007219
Valid tyre size	7.00 - 12
LI / SI / PR	130 A8, 14 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 75 A
Ventilposition	central
Brand	BKT
Tread pattern	PL 801
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	19,42
Recommended rim size	5.00S
Maximum air pressure [bar].	9,00
Section width (mm)	189
Outer diameter of tyre [mm].	692
Tread depth (mm)	15,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 A8	1900	40	Load wheel	9,00	
	2755	25	Load wheel	9,00	
	2120	25	Steering wheel	9,00	