# Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15771130
Valid tyre size	8.15 - 15
LI / SI / PR	142 A8, 14 PR
TL/TT	ТТ
SET	Tube + Flap
Brand	ВКТ
Tread pattern	PL 801



#### Notes and features

- The BKT PL 801 was developed for forklifts, but is equally suitable for hay tedders and hay harvesting equipment.
- The tyre is characterised by its excellent stability.
- Its rubber compound offers very good resistance to punctures and cuts, ensuring a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	15771130
EAN	8903094007271
Valid tyre size	8.15 - 15
Alternative size 1	28x9-15
LI / SI / PR	142 A8, 14 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 75 A
Ventilposition	central
Brand	ВКТ
Tread pattern	PL 801
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	25,02
Recommended rim size	7.0
Permitted rim size	7.00BD
Maximum air pressure [bar].	10,00
Section width (mm)	215
Outer diameter of tyre [mm].	720
Tread depth (mm)	19,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40	Steering wheel	10,00	
	3900	25	Load wheel	10,00	
	3000	25	Steering wheel	10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.