Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15771140
Valid tyre size	8.25 - 15
LI / SI / PR	145 A8, 14 PR
TL/TT	ТТ
SET	Tube + Flap
Brand	ВКТ
Tread pattern	PL 801



Notes and features

- The BKT PL 801 was developed for forklifts, but is equally suitable for hay tedders and hay harvesting equipment.
- The tyre is characterised by its excellent stability.
- Its rubber compound offers very good resistance to punctures and cuts, ensuring a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15771140
EAN	8903094007301
Valid tyre size	8.25 - 15
LI / SI / PR	145 A8, 14 PR
TL/TT	тт
SET	Tube + Flap
Valve designation	TR 177 A
Ventilposition	central
Brand	ВКТ
Tread pattern	PL 801
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	34,03
Recommended rim size	6.5
Permitted rim size	6.0, 7.0
Maximum air pressure [bar].	8,00
Section width (mm)	236
Outer diameter of tyre [mm].	854
Tread depth (mm)	18,0
E-Ready	No

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40	Steering wheel	8,00	
	4225	25	Load wheel	8,00	
	3250	25	Load wheel	8,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.