

TYRES

Product group	Tyres
Item number	15771155
Valid tyre size	250 - 15
LI / SI / PR	20 PR
TL/TT	TT
SET	Tube + Flap
Brand	BKT
Tread pattern	PL 801



Notes and features

- The BKT PL 801 was developed for forklifts, but is equally suitable for hay tedders and hay harvesting equipment.
- Its rubber compound offers very good resistance to punctures and cuts, ensuring a long service life.
- The tyre is characterised by its excellent stability.

Technical Informations

Item number	15771155
EAN	8903094007066
Valid tyre size	250 - 15
Alternative size 1	250/70-15
LI / SI / PR	20 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 77 A
Ventilposition	central
Brand	BKT
Tread pattern	PL 801
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	33,92
Recommended rim size	7.50BD
Permitted rim size	7.0, 7.5
Maximum air pressure [bar].	10,00
Section width (mm)	235
Outer diameter of tyre [mm].	745
Tread depth (mm)	19,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	5040	25	Load wheel	10,00	
	3875	25	Steering wheel	10,00	