

TYRES

Product group	Tyres
Item number	15771160
Valid tyre size	300 - 15
LI / SI / PR	18 PR
TL/TT	ТТ
SET	Tube + Flap
Brand	ВКТ
Tread pattern	PL 801



Notes and features

- The BKT PL 801 was developed for forklifts, but is equally suitable for hay tedders and hay harvesting equipment.
- The tyre is characterised by its excellent stability.
- Its rubber compound offers very good resistance to punctures and cuts, ensuring a long service life.



Technical Informations

Item number	15771160
EAN	8903094007080
Valid tyre size	300 - 15
Alternative size 1	315/70-15
LI / SI / PR	18 PR
TL/TT	ТТ
SET	Tube + Flap
Valve designation	TR 77 A
Ventilposition	central
Brand	BKT
Tread pattern	PL 801
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	46,59
Recommended rim size	8.00BD
Permitted rim size	8.0
Maximum air pressure [bar].	7,50
Section width (mm)	295
Outer diameter of tyre [mm].	840
Tread depth (mm)	23,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	5850	25	Load wheel	7,50	
	4500	25	Steering wheel	7,50	