

## **TYRES**

Product group	Tyres	
Item number	15771195	
Valid tyre size	12.00 - 20	
LI / SI / PR	185 A2, 20 PR	
TL/TT	тт	
SET	Tube + Flap	
Brand	ВКТ	
Tread pattern	Power Trax HD Smooth	





## Notes and features

- The Power Trax HD Smooth has been specially designed for use in ports and underground mining.
- The tyre is characterised by its high load capacity.
- The reinforced sidewalls and the special tread compound provide excellent protection against cut and puncture damages.



## **Technical Informations**

Item number	15771195
EAN	8903094007882
Valid tyre size	12.00 - 20
LI / SI / PR	185 A2, 20 PR
TL/TT	тт
SET	Tube + Flap
Ventilposition	central
Brand	BKT
Tread pattern	Power Trax HD Smooth
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	110,18
Recommended rim size	8.50
Permitted rim size	9.0
Maximum air pressure [bar].	10,00
Section width (mm)	320
Outer diameter of tyre [mm].	1150
Tread depth (mm)	34,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 A2	9250	10	Load wheel	10,00	
	9230	25	Steering wheel	10,00	
	7100	25		10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.