

TYRES

Product group	Tyres
Item number	15772121
Valid tyre size	10 - 16.5
LI / SI / PR	120 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	Skid Power SK



Notes and features

- BKT's Skid Power SK tyre is a newly-developed wide-wall skid steer loader tyre.
- With sidewall and rim guard protectors, the Skid Power SK is ideal for performance-oriented and price-conscious use on skid steer loaders like the Bobcat and other similar vehicles.



Technical Informations

Item number	15772121
EAN	8903094055715
Valid tyre size	10 - 16.5
LI / SI / PR	120 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	Skid Power SK
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	21,95
Recommended rim size	8.25
Maximum air pressure [bar].	5,20
Section width (mm)	270
Outer diameter of tyre [mm].	775
Stat. radius (SLR) [mm]	355
Rolling circumference [mm].	2286
Tread depth (mm)	15,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 A8	1400	40		5,20	
	1560	25		5,20	
	2135	10		5,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.