

TYRES

Product group	Tyres
Item number	15772148
Valid tyre size	12 - 16.5
LI / SI / PR	147 A2, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	Giant Trax



Bohnenkamp
Moving Professionals



Notes and features

- The Giant Trax features a special deep tread pattern with large and robust tread blocks providing good traction and a long service life
- The smooth tread pattern allows for increased ground contact and increased stability
- The special rubber compound provides for excellent cutting and tearing resistance
- The extra thick side wall with rim protection prevents damage
- Sturdy nylon casing offering outstanding puncture resistance
- Suitable for skid steer loaders and similar vehicles

Technical Informations

Item number	15772148
EAN	8903094045860
Valid tyre size	12 - 16.5
LI / SI / PR	147 A2, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	Giant Trax
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	47,66
Recommended rim size	9.75
Maximum air pressure [bar].	6,20
Section width (mm)	315
Outer diameter of tyre [mm].	840
Stat. radius (SLR) [mm]	398
Rolling circumference [mm].	2521
Tread depth (mm)	36,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A2	3075	10		6,20	
	2245	25		6,20	