

TYRES

Product group	Tyres	
Item number	15772149	
Valid tyre size	12 - 16.5	
LI / SI / PR	145 A2, 12 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Power Trax HD Skid Steer	





Notes and features

- The BKT Power Trax HD Skid Steer has been specially designed for skid steer loaders.
- Its deep tread pattern, extra thick sidewalls and tough casing protect the tyre from cuts, tears and punctures.
- The tyre is characterised by outstanding durability and is especially suitable for rough and hard concrete surfaces.
- It is ideal for use in scrap yards, recycling operations, mining etc.



Technical Informations

Item number	15772149
EAN	8903094017355
Valid tyre size	12 - 16.5
LI / SI / PR	145 A2, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Power Trax HD Skid Steer
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	46,70
Recommended rim size	9.75
Maximum air pressure [bar].	5,50
Section width (mm)	324
Outer diameter of tyre [mm].	865
Stat. radius (SLR) [mm]	391
Rolling circumference [mm].	2552
Tread depth (mm)	34,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A2	2900	10		5,50	
	2090	25		5,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.