

TYRES

Product group	Tyres
Item number	15772202
Valid tyre size	8.25 - 20
LI / SI / PR	133 B, 14 PR
TL/TT	TT
SET	Tube + Flap
Brand	BKT
Tread pattern	EM 936



Notes and features

- A robust tyre for wheeled excavators in the toughest operating conditions.
- Well suited for road transport.
- Aggressive tread pattern for high traction and good self-cleaning properties.
- High stability in use and good handling on the road.

Technical Informations

Item number	15772202
EAN	8903094005383
Valid tyre size	8.25 - 20
LI / SI / PR	133 B, 14 PR
TL/TT	TT
SET	Tube + Flap
Ventilposition	central
Brand	BKT
Tread pattern	EM 936
TRA Code	E2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	38,16
Recommended rim size	6.5
Permitted rim size	6.0, 7.0
Maximum air pressure [bar].	6,75
Section width (mm)	235
Outer diameter of tyre [mm].	980
Stat. radius (SLR) [mm]	467
Rolling circumference [mm].	2970
Tread depth (mm)	18,0
Number of lugs	25x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 B	2060	50		6,75	