

TYRES

Product group	Tyres
Item number	15772219
Valid tyre size	10.00 - 20
LI / SI / PR	14 PR
TL/TT	TT
Brand	BKT
Tread pattern	Lug Star



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Lug Star is a specially developed tyre for wheeled excavators.
- With its closed, robust tread center, the tire is excellently suited for use on two-way excavators in rail traffic.

Technical Informations

Item number	15772219
EAN	8903094056828
Valid tyre size	10.00 - 20
LI / SI / PR	14 PR
TL/TT	TT
Brand	BKT
Tread pattern	Lug Star
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	55,75
Recommended rim size	7.5
Permitted rim size	7.0, 8.0
Maximum air pressure [bar].	5,00
Section width (mm)	280
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	506
Rolling circumference [mm].	3343
Tread depth (mm)	22,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	2470	50		5,00	