

TYRES

Product group	Tyres
Item number	15772222
Valid tyre size	10.00 - 20
LI / SI / PR	146 B, 16 PR
TL/TT	TT
SET	Tube + Flap
Brand	BKT
Tread pattern	EM 936



Notes and features

- A robust tyre for wheeled excavators in the toughest operating conditions.
- Well suited for road transport.
- Aggressive tread pattern for high traction and good self-cleaning properties.
- High stability in use and good handling on the road.

Technical Informations

Item number	15772222
EAN	8903094005314
Valid tyre size	10.00 - 20
LI / SI / PR	146 B, 16 PR
TL/TT	TT
SET	Tube + Flap
Ventilposition	central
Brand	BKT
Tread pattern	EM 936
TRA Code	E2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	53,00
Recommended rim size	7.5
Permitted rim size	7.0, 8.0
Maximum air pressure [bar].	7,50
Section width (mm)	275
Outer diameter of tyre [mm].	1050
Stat. radius (SLR) [mm]	498
Rolling circumference [mm].	3180
Tread depth (mm)	24,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 B	3000	50		7,50	