

TYRES

Product group	Tyres
Item number	15772223
Valid tyre size	10.00 - 20
LI / SI / PR	146 B, 16 PR
TL/TT	тт
SET	Tube + Flap
Brand	BKT
Tread pattern	EM 936 Super



Notes and features

- The BKT EM 936 Super is a rugged tyre for mobile excavators in the harshest operating conditions
- Well-suited for road travel
- The aggressive tread pattern enables high traction and good self-cleaning properties
- The tyre provides outstanding stability in use and good handling on the road
- Its tread pattern is enlarged by 8-10% (extra wide) compared with the EM 936 for even more traction and ride comfort



Technical Informations

Item number	15772223
EAN	8903094062690
Valid tyre size	10.00 - 20
LI / SI / PR	146 B, 16 PR
TL/TT	TT
SET	Tube + Flap
Ventilposition	central
Brand	BKT
Tread pattern	EM 936 Super
TRA Code	E2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	57,54
Recommended rim size	7.5
Permitted rim size	7.0, 8.0
Maximum air pressure [bar].	7,50
Section width (mm)	277
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3336
Tread depth (mm)	21,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 B	3000	50		7,50	