

## TYRES

Product group	Tyres
Item number	15772242
Valid tyre size	16.0 / 70 - 20
LI / SI / PR	166 A2 / 149 B, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	EM 936



## Notes and features

- Rugged tyre for mobile excavators in the harshest of operating conditions.
- Well-suited for road travel.
- Aggressive tread pattern for high traction and good self-cleaning properties.
- High level of stability in use and good handling on the road.

## Technical Informations

Item number	15772242
EAN	8903094005345
Valid tyre size	16.0 / 70 - 20
Alternative size 1	400/70-20
LI / SI / PR	166 A2 / 149 B, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	EM 936
TRA Code	E2/L2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	58,25
Recommended rim size	13SDC
Permitted rim size	13
Maximum air pressure [bar].	4,50
Section width (mm)	405
Outer diameter of tyre [mm].	1090
Stat. radius (SLR) [mm]	480
Rolling circumference [mm].	3295
Tread depth (mm)	24,0
Number of lugs	21x2
Tyre capacity 75% [litr.]	183.1
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A2	5300	10		4,50	
149 B	3250	50		3,50	