

## TYRES

Product group	Tyres
Item number	15772250
Valid tyre size	16.0 / 70 - 24
LI / SI / PR	169 A2 / 152 B, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	EM 936



## Notes and features

- Rugged tyre for mobile excavators in the harshest of operating conditions.
- Well-suited for road travel.
- Aggressive tread pattern for high traction and good self-cleaning properties.
- High level of stability in use and good handling on the road.

## Technical Informations

Item number	15772250
EAN	8903094005369
Valid tyre size	16.0 / 70 - 24
Alternative size 1	400/70-24
LI / SI / PR	169 A2 / 152 B, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	EM 936
TRA Code	E2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	74,77
Recommended rim size	13SDC
Permitted rim size	13(DC)
Maximum air pressure [bar].	4,50
Section width (mm)	410
Outer diameter of tyre [mm].	1190
Stat. radius (SLR) [mm]	575
Rolling circumference [mm].	3600
Tread depth (mm)	30,0
Number of lugs	24x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A2	5800	10		4,50	
152 B	3550	50		3,50	