Bohnenkamp Moving Professionals

20.09.2024

TYRES

| Product group | Tyres | |
|-----------------|-----------------------|--|
| Item number | 15772260 | |
| Valid tyre size | 20 - 24 | |
| LI / SI / PR | 173 A2 / 158 B, 12 PR | |
| TL/TT | TL | |
| Brand | ВКТ | |
| Tread pattern | EM 936 | |



Notes and features

- Rugged tyre for mobile excavators in the harshest of operating conditions.
- Well-suited for road travel.

- Aggressive tread pattern for high traction and good selfcleaning properties.
- High level of stability in use and good handling on the road.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 15772260 |
|------------------------------|-----------------------|
| EAN | 8903094026210 |
| Valid tyre size | 20 - 24 |
| Alternative size 1 | 22/70-24 |
| LI / SI / PR | 173 A2 / 158 B, 12 PR |
| TL/TT | TL |
| Brand | ВКТ |
| Tread pattern | EM 936 |
| TRA Code | E2/L2/G2 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 141,14 |
| Recommended rim size | 16.00T SDC |
| Maximum air pressure [bar]. | 3,00 |
| Section width (mm) | 535 |
| Outer diameter of tyre [mm]. | 1390 |
| Stat. radius (SLR) [mm] | 665 |
| Rolling circumference [mm]. | 4205 |
| Tread depth (mm) | 30,0 |
| Number of lugs | 23x2 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 173 A2 | 6500 | 10 | | 3,00 | |
| 158 B | 4250 | 50 | | 2,50 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.