

TYRES

Product group	Tyres
Item number	15772283
Valid tyre size	9.5 / 65 - 15
LI / SI / PR	118 A2, 6 PR
TL/TT	тт
Brand	ВКТ
Tread pattern	Pac Master



Notes and features

- The BKT Compactor series is designed to distribute ground pressure evenly and achieve optimum compaction.
- The specially developed tread compound can withstand high temperatures.
- Adhesions caused by loose materials are kept to a minimum due to the closed tread pattern (smooth).
- Most suitable for use with compaction rollers and similar vehicles.



Technical Informations

Item number	15772283
EAN	8903094036141
Valid tyre size	9.5 / 65 - 15
LI / SI / PR	118 A2, 6 PR
TL/TT	т
Brand	ВКТ
Tread pattern	Pac Master
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	25,53
Recommended rim size	7.0
Maximum air pressure [bar].	3,25
Section width (mm)	235
Outer diameter of tyre [mm].	675
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 A2	1320	10		3,25	
	1060	15		3,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.