

TYRES

Product group	Tyres
Item number	15772310
Valid tyre size	9.00 - 20
LI / SI / PR	156 A2, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	Pac Master



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT Compactor series is designed to distribute ground pressure evenly and achieve optimum compaction.
- The specially developed tread compound can withstand high temperatures.
- Adhesions caused by loose materials are kept to a minimum due to the closed tread pattern (smooth).
- Most suitable for use with compaction rollers and similar vehicles.

Technical Informations

Item number	15772310
EAN	8903094002627
Valid tyre size	9.00 - 20
LI / SI / PR	156 A2, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	Pac Master
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	46,37
Recommended rim size	7
Permitted rim size	7.5
Maximum air pressure [bar].	6,25
Section width (mm)	275
Outer diameter of tyre [mm].	1016
Stat. radius (SLR) [mm]	471
Rolling circumference [mm].	3107
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A2	4000	10		6,20	
	3150	15		6,25	