

## **TYRES**

Product group	Tyres
Item number	15772330
Valid tyre size	11.00 - 20
LI / SI / PR	169 A2, 18 PR
TL/TT	тт
Brand	BKT
Tread pattern	Pac Master



## Notes and features

- The BKT Compactor series is designed to distribute ground pressure evenly and achieve optimum compaction.
- The specially developed tread compound can withstand high temperatures.
- Adhesions caused by loose materials are kept to a minimum due to the closed tread pattern (smooth).
- Most suitable for use with compaction rollers and similar vehicles.



## **Technical Informations**

Item number	15772330
EAN	8903094002498
Valid tyre size	11.00 - 20
LI / SI / PR	169 A2, 18 PR
TL/TT	ТТ
Brand	BKT
Tread pattern	Pac Master
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,76
Recommended rim size	8
Permitted rim size	8.5
Maximum air pressure [bar].	8,25
Section width (mm)	291
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	494
Rolling circumference [mm].	3310
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A2	5800	10		8,25	
	4625	15		8,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.