

TYRES

Product group	Tyres
Item number	15772331
Valid tyre size	11.00 - 20
LI / SI / PR	169 A2, 18 PR
TL/TT	TT
Brand	BKT
Tread pattern	Pac Master



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT Compactor series is designed to distribute ground pressure evenly and achieve optimum compaction.
- The specially developed tread compound can withstand high temperatures.
- Adhesions caused by loose materials are kept to a minimum due to the closed tread pattern (smooth).
- Most suitable for use with compaction rollers and similar vehicles.

Technical Informations

Item number	15772331
EAN	8903094067169
Valid tyre size	11.00 - 20
LI / SI / PR	169 A2, 18 PR
TL/TT	TT
Brand	BKT
Tread pattern	Pac Master
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	66,18
Recommended rim size	8.0
Permitted rim size	8.5
Maximum air pressure [bar].	8,25
Section width (mm)	291
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	494
Rolling circumference [mm].	3310
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A2	5800	10		8,25	
	4625	15		8,25	