Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15772440	
Valid tyre size	23.1 - 26	
LI / SI / PR	164 A6, 12 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	TR 387	



Notes and features

- Suitable for rollers, fruit cultivation, golf carts and on lawns.
- Rounded lugs protect turf.

- Rugged casing.
- Long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15772440
EAN	8903094005154
Valid tyre size	23.1 - 26
LI / SI / PR	164 A6, 12 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	TR 387
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	150,06
Recommended rim size	DW20B
Maximum air pressure [bar].	1,70
Section width (mm)	592
Outer diameter of tyre [mm].	1560
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4688
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A6	5000	30		1,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.