Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15772442	
Valid tyre size	18.4 - 26	
LI / SI / PR	146 A6, 12 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	TR 387	



Notes and features

- Suitable for rollers, fruit cultivation, golf carts and on lawns.
- Rounded lugs protect turf.

- Rugged casing.
- Long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15772442
EAN	8903094005000
Valid tyre size	18.4 - 26
LI / SI / PR	146 A6, 12 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	TR 387
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,83
Recommended rim size	DW16L
Permitted rim size	DW15L
Maximum air pressure [bar].	2,30
Section width (mm)	475
Outer diameter of tyre [mm].	1430
Stat. radius (SLR) [mm]	635
Rolling circumference [mm].	4150
Tread depth (mm)	24,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A6	3000	30		2,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.