

TYRES

Product group	Tyres
Item number	15772455
Valid tyre size	28 L - 26
LI / SI / PR	154 A6 / 150 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 390



Notes and features

- Industrial bias tyre with block tread pattern for varying uses, e.g. road construction on drum compactors, on industrial tractors or in agriculture and landscape management on different machines and heavy equipment.
- Wide tread pattern block and rounded shoulders guarantee optimal soil protection and good surface contact for good propulsion.
- Increased tread pattern depth and reinforced casing for a longer service life.

Technical Informations

Item number	15772455
EAN	8903094005239
Valid tyre size	28 L - 26
LI / SI / PR	154 A6 / 150 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 390
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	166,36
Recommended rim size	25.0
Permitted rim size	23
Maximum air pressure [bar].	1,40
Section width (mm)	714
Outer diameter of tyre [mm].	1560
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4545
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A6	3750	30		1,40	
150 A8	3350	40		1,40	