

TYRES

Product group	Tyres
Item number	15772457
Valid tyre size	28 L - 26
LI / SI / PR	172 A6 / 168 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 390



Notes and features

- Industrial bias tyre with block tread pattern for varying uses, e.g. road construction on drum compactors, on industrial tractors or in agriculture and landscape management on different machines and heavy equipment.
- Wide tread pattern block and rounded shoulders guarantee optimal soil protection and good surface contact for good propulsion.
- Increased tread pattern depth and reinforced casing for a longer service life.

Technical Informations

Item number	15772457
EAN	8903094047048
Valid tyre size	28 L - 26
LI / SI / PR	172 A6 / 168 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 390
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	192,87
Recommended rim size	DW25B
Permitted rim size	DW23B
Maximum air pressure [bar].	2,80
Section width (mm)	714
Outer diameter of tyre [mm].	1560
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4545
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A6	6300	30		2,80	
168 A8	5600	40		2,80	