

TYRES

Product group	Tyres
Item number	15772475
Valid tyre size	9 - 14.5
LI / SI / PR	12 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	LP 450





Notes and features

- The BKT LP 450 is a bias EM tyre for industrial use
- It was developed for transport applications on construction sites.



Technical Informations

Item number	15772475
EAN	8903094008322
Valid tyre size	9 - 14.5
LI / SI / PR	12 PR
TL/TT	TL
Brand	BKT
Tread pattern	LP 450
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	18,54
Recommended rim size	7.00MH
Maximum air pressure [bar].	6,90
Section width (mm)	246
Outer diameter of tyre [mm].	712
Stat. radius (SLR) [mm]	322
Rolling circumference [mm].	2115
Tread depth (mm)	9,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	1500	100		6,90	
	1320	100		6,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.