

TYRES

Product group	Tyres
Item number	15772490
Valid tyre size	33 x 12.50 - 15
LI / SI / PR	134 A2, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	AT 621



Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear- and cut-resistant rubber compound.
- For use on backhoe loaders, wheel loaders and other vehicles.

Technical Informations

Item number	15772490
EAN	8903094037209
Valid tyre size	33 x 12.50 - 15
LI / SI / PR	134 A2, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	AT 621
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	34,50
Recommended rim size	10.00F SDC
Maximum air pressure [bar].	3,25
Section width (mm)	318
Outer diameter of tyre [mm].	851
Stat. radius (SLR) [mm]	385
Rolling circumference [mm].	2493
Tread depth (mm)	22,0
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A2	2120	10		3,25	