

## TYRES

Product group	Tyres
Item number	15772510
Valid tyre size	10.5 / 80 - 18
LI / SI / PR	119 A8 / 131 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 603



## Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear and cut-resistant rubber compound
- For use on excavators, wheel and telescopic loaders

## Technical Informations

Item number	15772510
EAN	8903094019526
Valid tyre size	10.5 / 80 - 18
Alternative size 1	280/80-18
LI / SI / PR	119 A8 / 131 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 603
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	30,68
Recommended rim size	W9
Permitted rim size	W8, 9
Maximum air pressure [bar].	3,70
Section width (mm)	274
Outer diameter of tyre [mm].	907
Stat. radius (SLR) [mm]	422
Rolling circumference [mm].	2727
Tread depth (mm)	21,5
Number of lugs	18x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
119 A8	1360	40	Drive Wheel	3,70	LLV
131 A8	1950	40	Free Rolling	3,70	LLV