

## TYRES

Product group	Tyres
Item number	15772515
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	129 A8 / 142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621 (Industrial)



## Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear and cut-resistant rubber compound
- For use on backhoe loaders, wheel loaders and similar vehicles.

**Technical Informations**

Item number	15772515
EAN	8903094019731
Valid tyre size	12.5 / 80 - 18
Alternative size 1	340/80-18
LI / SI / PR	129 A8 / 142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621 (Industrial)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	46,29
Recommended rim size	W9
Permitted rim size	11.0
Maximum air pressure [bar].	5,10
Section width (mm)	308
Outer diameter of tyre [mm].	987
Stat. radius (SLR) [mm]	434
Rolling circumference [mm].	2916
Tread depth (mm)	28,0
Number of lugs	20x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40	Free Rolling	5,10	
129 A8	1850	40	Drive Wheel	5,10	