

## TYRES

|                 |                        |
|-----------------|------------------------|
| Product group   | Tyres                  |
| Item number     | 15772520               |
| Valid tyre size | 12.5 / 80 - 18         |
| LI / SI / PR    | 129 A8 / 142 A8, 12 PR |
| TL/TT           | TL                     |
| Brand           | BKT                    |
| Tread pattern   | AT 603                 |



## Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear and cut-resistant rubber compound
- For use on excavators, wheel and telescopic loaders

**Technical Informations**

|                              |                        |
|------------------------------|------------------------|
| Item number                  | 15772520               |
| EAN                          | 8903094019595          |
| Valid tyre size              | 12.5 / 80 - 18         |
| Alternative size 1           | 340/80-18              |
| LI / SI / PR                 | 129 A8 / 142 A8, 12 PR |
| TL/TT                        | TL                     |
| Brand                        | BKT                    |
| Tread pattern                | AT 603                 |
| Antistatic                   | No                     |
| Tyre colour                  | Black                  |
| ECE regulation number        | ECE 106                |
| Nettogewicht [kg] (gültig)   | 41,99                  |
| Recommended rim size         | W9                     |
| Permitted rim size           | W11                    |
| Maximum air pressure [bar].  | 3,70                   |
| Section width (mm)           | 308                    |
| Outer diameter of tyre [mm]. | 987                    |
| Stat. radius (SLR) [mm]      | 448                    |
| Rolling circumference [mm].  | 3027                   |
| Tread depth (mm)             | 27,5                   |
| Number of lugs               | 16x2                   |
| E-Ready                      | No                     |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 129 A8 | 1850               | 40           | Drive Wheel   | 3,70                     | LLV          |
| 142 A8 | 2650               | 40           | Free Rolling  | 3,70                     | LLV          |