Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres
Item number	15772531
Valid tyre size	15.5 / 60 - 18
LI / SI / PR	141 A2, 12 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	AT 621





Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear and cut-resistant rubber compound
- For use on backhoe loaders, wheel loaders and similar vehicles.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15772531
EAN	8903094048229
Valid tyre size	15.5 / 60 - 18
LI / SI / PR	141 A2, 12 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	AT 621
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	45,06
Recommended rim size	W13
Permitted rim size	13
Maximum air pressure [bar].	3,00
Section width (mm)	394
Outer diameter of tyre [mm].	940
Stat. radius (SLR) [mm]	428
Rolling circumference [mm].	2871
Tread depth (mm)	22,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A2	2575	10		3,00	
	1930	35		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.