

TYRES

Product group	Tyres
Item number	15772533
Valid tyre size	15.5 / 70 - 18
LI / SI / PR	143 A2, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621





Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear and cut-resistant rubber compound
- For use on backhoe loaders, wheel loaders and similar vehicles.



Technical Informations

Item number	15772533
EAN	8903094041602
Valid tyre size	15.5 / 70 - 18
Alternative size 1	400/70-18
LI / SI / PR	143 A2, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	51,54
Recommended rim size	W13
Maximum air pressure [bar].	2,60
Section width (mm)	400
Outer diameter of tyre [mm].	1030
Stat. radius (SLR) [mm]	474
Rolling circumference [mm].	3111
Tread depth (mm)	23,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A2	2725	10		2,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.