

## TYRES

Product group	Tyres
Item number	15772536
Valid tyre size	380 / 75 - 20
LI / SI / PR	148 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star



## Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

## Technical Informations

Item number	15772536
EAN	8903094051519
Valid tyre size	380 / 75 - 20
Alternative size 1	14.5-20
LI / SI / PR	148 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,25
Recommended rim size	W12
Permitted rim size	W11, 12D, 12, W13, 13D, 13
Maximum air pressure [bar].	4,00
Section width (mm)	385
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3273
Tread depth (mm)	31,5
Number of lugs	17x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		4,00	