Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15772537
Valid tyre size	400 / 70 - 20
LI / SI / PR	149 A8, 16 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Con Star



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15772537
EAN	8903094043323
Valid tyre size	400 / 70 - 20
Alternative size 1	16.0/70-20
LI / SI / PR	149 A8, 16 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	66,53
Recommended rim size	13
Permitted rim size	12SDC, 13SDC, 14
Maximum air pressure [bar].	4,00
Section width (mm)	405
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	501
Rolling circumference [mm].	3303
Tread depth (mm)	33,5
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.